SMART Wall Bracket For Hotel Toiletries



Designed in Vietnam - Made in Vietnam



# From aircraft maintenance to wall-brackets

Our products were designed by a father and son team in Vietnam. The father worked as a maintenance technician for Vietnam Airlines from 197 to ... While the son in engineering for several 5-star hotels in Vietnam.

They have been producing premium aluminium accessories for brands such as Range Rover as well as motorcycle brands from the UK.

Realizing the need for elegant and yet temper-proof wall-mounts they have designed several different products one of which has been registered for design patent protection.

All our wall-mounts are made with top quality 5052aluminium which is rust proof.

Our products come with a one-year limited warranty.



# Leonardo

Made from high quality anodized Aluminium 5052. **Rust proof** 

Glass bead peening. Silky smooth surface

Temper proof design. Side locking. Safe for hotels

Can be affixed to walls with 3M VHB tape. No drilling.

0 Side Locking

Side locking

# Donatello

Made from high quality anodized Aluminium 5052. **Rust proof** 

Glass bead peening. Silky smooth surface

Temper proof design. Front locking. Safe for hotels

Can be affixed to walls with 3M VHB tape. No drilling.

Front locking



Front Locking

# Karai

Made from high quality anodized Aluminium 5052. **Rust proof** 

Glass bead peening. Silky smooth surface

Can be affixed to walls with 3M VHB tape. No drilling.

Material : Aluminium 5052 frame 3mm, cups 1mm

Weight : only 380g for a 500ml triple-container



# WALL MOUNTS 3M VHB Tape 5952


How to apply the 3M VHB Tape?

To obtain optimum adhesion, the bonding surfaces must be well unified, clean and dry. Typical surface cleaning solvents are IPA/ water mixture (rubbing alcohol) or heptane. Firm application pressure develops better adhesive contact and helps improve bond strength. After application, the bond strength will increase as the adhesive flows onto the surface. At room temperature, approximately 50% of the ultimate strength will be achieved after 20 minutes, 90% after 24 hours and 100% after 72 hours.

## Do I need to use a primer

Glass, stone, ceramic or other siliceous materials are hydrophilic by nature. 3M Silane coupling agents, added to the IPA/water cleaning solution, can help reduce the "water-loving" tendency of these surfaces and enhance the tape bond in high moisture environments.

How much weight can the 3M VHB Tape hold?



Step C: Apply tape to surface



Step D: Roll finished joint

The 3M VHB Tape can hold up to 10 kilogram





Step A: Solvent wipe

Step B: Wipe dry

# WALLMOUNTS | Silicone Glue

#### How to apply Silicone Glue?

To obtain optimum adhesion, the bonding surfaces must be well unified, clean and dry. Remove any dirt and grime from the wall using cleaning fluid and a soft cloth. Add silicone to the wall mount and fix the wall mount on the wall. Push gently in the centre, working out towards the edges so that the silicone spreads. Give the silicone 24 hours to set properly.

#### How long will the Silicone Glue last?

Silicone will last around 10 years, depending on factors such as temperature, UV light, exposure, and chemical properties of the metal. Silicone provides protection against the negative impacts of moisture and water.

#### How much weight can Silicone Glue hold?

Silicone Glue can hold up to 10 kilogram







Step A: Clean surface Step B: Apply Silicone Step C: Wait 24hrs

## **One Year Limited Warranty**

Natural Joint Stock Company warrants to the original purchaser of each Dispenser that all parts, excluding any tape, glue or silicone that maybe included, shall be free from defects in material and workmanship under normal use and service for a period of one (1) year from the date of shipment to the original purchaser.

Our Dispensers are rated for products within a viscosity range of 150mPas - 50,000mPas. J.R.S Natural Joint Stock Company cannot guarantee proper operation of the dispensers if your product falls outside this range. Use of products outside of the approved viscosity range shall invalidate all warranties contained herein.

The warranties defined herein shall not apply to any damage or defects created or arising from accident, misapplication, abuse, misuse, neglect, alteration, acts of God, vandalism, flood, fire or any other occurrences beyond the control of Natural Joint Stock Company.

Claims under the forgoing warranty will be honored only Natural Joint Stock Company (i) has received the entire payment of the purchase price for the product with respect to which any such claim is made, (ii) has received notification of the claim prior to the expiration of the one (1) year warranty period described above, (iii) has received the returned product delivered duty paid and the detailed description of the defect, and (iv) determines upon examination of the returned product that it is defective under the terms of such warranty.

Natural Joint Stock Company's sole obligation under the forgoing warranty and for other claims related to any product shall be limited to, at Natural Joint Stock Company's option, (i) repairing or (ii) replacing, Exworks HCMC, Vietnam any product we determines is defective under the terms of such warranty.

The foregoing warranty and remedies are exclusive and in lieu of any other warranties and remedies whatsoever, expressed or implied, including but not limited to any implied warranties of merchantability or fitness for a particular purpose, all of which Natural Joint Stock Company hereby expressly disclaims. Natural Joint Stock Company is not responsible for incidental or consequential damages of any kind, including but not limited to lost profits, downtime, goodwill or damage to equipment or property.





#### Cong Ty Co Phan Thien Nhien

Saigon Centre 67 Le Loi street District 1 HCMC Vietnam

#### Factory

Standard Factory B Tan Thuan Export Zone District 7 HCMC Vietnam

info@njscvietnam.com www.spapure.vn